

Applicable requirements : Standard(s) for Electric Vacuum Cleaning Machines and Blower Cleaners (UL-1017)

For the Collection of Combustible Dust, proceed with a Dust Hazard Analysis (DHA) as per NFPA 652 - 2016



- Intermittent Housekeeping and General Cleaning.
- HEPA Filter Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001 H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- Designed for General Sanding Applications
- Equipped with a 4-stage filtration system
- For dry recovery only
- Stainless Steel recovery tank.
- Convenient storage rack and tool basket
- Convenient design allows easy access to HEPA Filter while maintaining a leak proof seal
- Very silent only 63 dB(A)
- Mounted on a 4-wheel dolly for easy maneuverability.
- Tiger-Vac® holds a large selection of optional dustless hand tools.



Specifications

AS-400 ECO HEPA SK	112418A
Model Name	AS-400 ECO HEPA SK
Type (Powerhead)	Electric
Voltage	120 V
Hertz	60 Hz
Phase	Single
Wattage	1260 W
Power	1.7 HP
Amperage	10.5 amps.
Air Flow	128 CFM
Vacuum Pressure	107 " H ₂ 0
Sound Level	63 dB(A)
Plug Type	120V
Suction Inlet	1.5 "
Cart Type	2+2 Wheels
Filter Cleaning	None
Dry Recovery - Tank	10 Gal
Dry Recovery - Disposable Filter Bag	10 Gal
Length	20 "
Width	21 "
Weight (Vacuum Only)	38 lbs.
Height	54 "
Cord Length	33 ft.

Use only recommended tools & accessories



AS-400 ECO HEPA SK Automatic Remote Start/Stop - Included



HEPA Filter - Included



Clear Polyliner Recovery Bags - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included





Disposable Filter Bag - Included



Spark Trap - Optional

AS-400 ECO HEPA SK rear view



Tiger-Vac Inc. 11 SW 12th Ave #112 Dania, FL 33004 USA

U.S. Headquarters

Tel: 1-800-668-4437 (954-925-3625) Fax: 1-800-668-4439 (954-925-3626) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com

Applicable requirements : Standard(s) for Electric Vacuum Cleaning Machines and Blower Cleaners (UL-1017)



For the Collection of Combustible Dust,

proceed with a Dust Hazard Analysis (DHA) as per NFPA 652 - 2016

International Headquarters

Tiger-Vac International Inc.

Low Noise

Tel: (450-625-0099) Fax: (450-625-3388) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com



Dry Recovery

Specifications for AS-400 ECO HEPA SK

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank	Dry Recovery - Disposable Filter Bag
AS-400 ECO	112418A	120 V	60 Hz	Single	1260 W	1.7 HP	10.5 amps.	128 CFM	107 " H ₂ 0	120V	10 Gal	10 Gal
HEPA SK	Dimensions	/21" x L20"	Weigh	nt: 38 lbs.	Sound	Level: 63 dB	(A)					

2020 Dagenais Blvd. Ouest Laval, Quebec

Canada H7L 5W2

HEPA

HEPA

Included

High Efficiency

Please note that specifications are subject to change without notice

Technical Sheet for AS-400 ECO HEPA SK

HEPA FIL	EPA FILTER AND ACCESSORIES - Included					
Part #	Description					
212303	HEPA FILTER (H14)					
FILTERS	AND ACCESSORIES - Included					
Part #	Description					
212385S	MAIN FILTER ASSEMBLY WITH BLACK PLASTIC RING, SHORT (FOR DRY RECOVERY ONLY)					
212303F2	MICRO SAFETY FILTER (CLOTH) WITH ELASTIC, FOR USE WITH HEPA FILTER 212303					
SYNTHE	TIC RECOVERY BAGS - Included					
Part #	Description					
219186	COLLECTION BAGS, WHITE SYNTHETIC, 10 GAL (14.25" x 34"), FOR INLETS #219530 & #216906 (PACKAGE OF 5)					
-	•					

POLY LINER RECOVERY BAGS AND ACCESSORIES - Included					
Part #	Description				
213184M	POLY LINERS "NEST" FOR 12 AND 14 GALLON - NO HOLE (PACKAGE OF 5) INCLUDES TWIST TIES				

SPARK T	RK TRAP - Optional						
Part #	Description						
218910A	SPARK TRAP ASSEMBLY WITH ALUMINUM MESH FILTER INSTALLED, FOR USE w/38mm CONDUCTIVE PLASTIC INLET						

TOOLS AND ACCESSORIES - Included

Part # Description

303019D SUCTION/AIR HOSE STATIC CONDUCTIVE CRUSHPROOF 20'(6m) (15'x1.25" + 5'x1") w/6'(1.8m)SLEEVE